

Horizontal Bagging Powder Packing Machine HY-210-BP

Especificaciones :

Precio	Contact us
Nombre de la marca	Hanyi
Lugar de origen	China
Cantidad minima para ordenar	1
Términos de pago	T/T,L/C,D/P
Capacidad de suministro	100
Detalle de Envio	3days--7days
detalles del empaque	Wooden case or wooden pellets depended on clients' require

Introducción detallada :



Main functions

1. Reduce production costs and management costs: A packaging line can reduce 4-10 workers, and the input cost will be recovered within 1-2 years;
2. Improve the product grade: It can make the product appearance and packaging quality reach a unified standard.
3. Reduce the rate of defective products, and the rate of finished products can reach over 99.5%, avoiding the waste of manual packaging;
4. Improve hygiene standards: There is no direct contact with people during the packaging process to avoid human pollution.

Main features

1. Wide range of packaging: It is suitable for packaging powder materials such as flour, coffee, resin, and extract powder.

2. Easy to operate: It adopts PLC control and man-machine interface operating system to make the operation intuitive and convenient.
3. Easy to adjust: Variety change can be completed in about ten minutes.
4. Suitable for different types of packaging bags.
5. The perfect prevention system guarantees the yield rate and does not waste bags and materials.
6. The packaging part of the machine adopts stainless steel materials to ensure the hygiene and safety of the materials.
7. High degree of automation: In the whole process of weighing and packaging, unmanned operation is realized, and when failure occurs, it will automatically alarm.
8. Some imported engineering plastics are used.
9. No need to refuel, reducing the pollution of materials.
10. Adopt oil-free vacuum pump to avoid pollution of production environment.

Technical Parameters

Model	HY-210-BP
Packaging type	Flat bags, three-side seals, four-side seals, zipper bags, stand-up bags, etc.
Packing bag material	Composite film, PP, etc.
Packing bag size	W: 100-210mm, L: 150-300mm
Weight range	5-1500g
Packing speed	20-45 bags/min (The speed is determined by the material itself and filling weight)
Packing precision	±1%
Power supply	3.76KW, AC380V, 50Hz
Machine overall size	4200X1800X2400mm