

## **Scan Code Weighing Machine**

## **Especificaciones:**

| Precio                       | Contact us       |
|------------------------------|------------------|
| Nombre de la marca           | Hanyi            |
| Lugar de origen              | China            |
| Cantidad minima para ordenar | 1                |
| Términos de pago             | L/C, T/T, Paypal |
| Capacidad de suministro      | 1000             |
| Detalle de Envio             | 3days7days       |

## Introducción detallada:

## **Brief description**

Scanning and weighing all-in-one machine can effectively solve the application of online inspection of various sizes of cartons, packages, bottles, cans, bags, etc.

Whether the weight of the product can be weighed is qualified, it can detect the right or wrong of the relevant production record files of the product and make statistical management, and can optionally print various self-adhesive labels.

Our scan code weighing machine is made of stainless steel, with good waterproof and anti-corrosion. It is equipped with a food-grade conveyor belt, which can store data and connect to the ERP management system. It saves time and effort, and has high efficiency.

Model: HY-SC200 all-in-one machine





Scanning Weighing Machine for High-Performance Checkweighing

Our high-performance checkweigher helps prevent under- or over-filled products from reaching consumers. In addition, it reduces product waste and rework time, performs integrity checks on packaging components, and provides critical production data to improve processes.

**Technical parameters** 

| Model             | HY-SC200 |
|-------------------|----------|
| Maximum range g   | 200      |
| Minimum display g | 0.01     |



| Accuracy g (*)                        | +0.1   |  |
|---------------------------------------|--|--|
| Throughput* (bottles/min)             | 30   |  |
|                                       | 95   |  |
| Weighing belt width (mm)              |  |  |
| Weighing belt length (mm)             | 200  |  |
| Input length (mm)                     | 400  |  |
| Output length (mm)                    | 300  |  |
| Production line height (mm)           | H=850±50mm (can be customized)                   |  |
| Conveying Direction (Face to Display) | From left to right (can be customized)           |  |
| Rejection method                      | Air blow rejection                               |  |
| Base rack                             | Stainless steel                                  |  |
| Conveying roller                      | Anodized aluminum alloy                          |  |
| Conveying table top structural parts  | Anodized aluminum alloy                          |  |
| Conveyor Belt                         | Wear-resistant PU                                |  |
| Electric control cabinet              | Stainless steel wire drawing treatment           |  |
| Anchor bolts                          | Height adjustment: ±50 mm                        |  |
| Standard configuration                |  |  |
| Wind shield                           | Transparent acrylic (product height 35 mm)       |  |
| Collection device                     | Transparent acrylic                              |  |
| Scan code configuration               |  |  |
| Scan code collection speed            | 60tps  |  |
| Image Sensor                          | 838*640CM0S chip                                 |  |
| Status output                         | 5 pcs status LEDs and buzzer                     |  |
| Decoding performance                  | one-dimensional barcode,<br>two-dimensional code |  |