

Packaging Internal Pressure Tester HY-PI-01

Especificaciones :

Introducción detallada :

Product features

Technical parameters

Standard configuration

Product features

Automatic testing, automatic judgment of breakage, automatic return and automatic stop; automatic data processing.

Microcomputer control, 7-inch IPS high-definition touch screen, displaying test data and working status.

Supports two test modes of internal pressure method and external pressure method; it can perform dual test functions of pressure-holding test and burst test.

Intelligent configurations such as overload protection of the movement mechanism, automatic return, and power-off memory to ensure the safety of the user and the instrument itself.

Test data history records can be queried, the data cannot be changed, and the audit trail can comply with GMP management regulations.

Professional computer communication software, real-time display of the test, data analysis and processing, and data storage.

Compliant with standards: GB/T16491, GB4857.16, ASTM D642, ASTM D4169, TAPPIT804, ISO 2872, ISO 12048, JISZ0212.

Technical parameters

Pressure range: 0~3000N (other ranges can be customized)

Pressure range: 0 ~ 600kpa (other ranges can be customized)

Test height: 10 mm ~ 100 mm (other sizes can be customized)

Test size: 300mm×400mm

Dimensions: 550mm×460mm×600mm

Power supply: AC 220V, 50Hz

Weight: 65kg

Standard configuration

Host computer, micro printer, power cord, communication cable, professional measurement and control software.