

Customized water bottle label printing and labeling solution

Detail Pengenalan :

The solution is composed of two parts: An industrial-grade roll-to-roll color label printer HY210 and an automatic labeling machine, which realizes label printing and labeling function and makes customized water production easier and more efficient.

Part 1. Industrial-grade roll-to-roll color label printer HY210

Designed for high-resolution, high-speed, professional, and personalized color label printing, the price is within the acceptable range of most companies. With small investment, high return.

Widely used, production-oriented multi-faceted expert (customized water bottle label, shoe label, medicine label, chemical label, etc.)



Printing Width: maximum 215.9mm

Print resolution: maximum 1600dpi*1600dpi

Printing speed: up to 12 m/min

High-definition printing: 9m/min

Main features

1. Advanced Inkjet Memjet Printing Technology

Adopt advanced Memjet color page inkjet waterfall flow technology, can output 1600*1600dpi ultra high definition resolution.

Print clear and beautiful labels in a better form to improve label quality and brand image.



2. Ultra-definition imaging and brilliant colors



HY210 imaging effect



Other brand imaging effects

3. High speed, fast printing, fast printing speed, lower cost

Printing speed can reach 12 m/min

You can get about a thousand labels in a few minutes!



4. Large-capacity independent ink cartridges reduce waste and improve efficiency

Five large-capacity 200ml independent ink cartridges can reduce the need for frequent ink replenishment. A waste ink tank is needed to reduce waste, lower cost and better economic effect!



5. Low cost/convenient

Low cost on-demand printing to reduce waste and improve efficiency

Low cost-printing on demand, timely update, flexible use, effective control of printing costs



6. Convenient label custom software

Support all kinds of design software, from design to printing, print on demand anytime, anywhere.

Support label application software to realize variable data batch printing.

Support data variable printing and ERP system data access.



| | |
|--|--|
| Device model | HY210 |
| Printing technology | American Memjet color page inkjet waterfall flow technology |
| Printing speed | 203.2mm/sec (up to 12m/min) |
| Resolution | 1600*1600dpi |
| Media material width | 50.8-215.9mm |
| Printing width | 215.9mm |
| Data interface | USB2.0, Ethernet 10/100Base-T-T |
| Ink cartridge type | 5pcs of 200ml individual dye ink cartridges (CYMCK) |
| Print mode | Roll-to-roll, roll-to-roll cutting, print and save, fold paper |
| Bar code parameters | For Bar code, at least Class B (Code 39), bar width 10mils For QR code, at least Class B (PDF417), unit size 10mils |
| Body size | 510*285*385mm |
| Body weight | 30kg (including ink cartridge print head) |
| Consumables specifications | |
| Paper type | Gap paper, black mark paper, continuous paper |
| Paper thickness | 0.1-0.3mm |
| Printing media | Inkjet coated media, such as all kinds of synthetic paper, PET, PP |
| Included accessories | Printer*1, Inkjet printer head*1, USB cable*1, Power cord*1, Ink cartridges*1 |
| Warranty | One year |
| Optional accessories and post- printing supporting equipment | |
| Optional accessories | Roll feeder, Rewinder, Computer stand |

| | |
|-------------------------------------|---|
| Post- printing supporting equipment | Laminating machine Polishing and embossing machine Bronzing machine |
| Operating environment | |
| Power supply | 100-240V, peak current <4A |
| Print | 15-35C; Humidity: 20-80% |
| Storage | -5-50C; Humidity: 20-80% |
| System software | Windows-based design software, such as AI, CoreDraw, NiceLabel, BarTender, etc. |

Part 2. Fully Automatic Labeling Machine

This model is applicable to different kinds of round objects in pharmaceutical, cosmetic, food and other industries.



Main features

Intelligent control system:

Advanced PLC control system, servo labeling system, automatic label length detection and other high configurations to ensure the operation is stable and high speed.

Intelligent operating system:

Multi-functional man-machine operation interface, production counter, parameter adjustment and monitoring, with rich help function and fault display function.

Roll label device:

It can choose the removable plastic belt or industrial synchronous belt to achieve roll label function depending on different bottle surface characteristics.

Sending and collecting device

Machine can be operated alone with turntable and collection device, it can also be directly connected to production line.

Printer device:

Flexible options such as thermal transfer printer or inkjet printer are optional to complete the coding and labeling functions simultaneously.

Optional function:

Zebra PAX4, 105SL print engine;

Avery 924 print engine;

Bar code detection;

Label detection;

Remaining labels alarming function.

Specification

| | | | |
|---------------------|---|------------------------|--|
| Label objects size | Diameter: Φ 20-100mm Height: 30-260mm | Voltage | 220VAC \pm 10% 50Hz0.6Kw |
| Label size | Length: 10-300mm Height: 10-140mm | Air pressure | 0.6Mpa |
| Labeling speed | 100-250pcs/min (Depending on material and label size) | Applicable Environment | Temperature: 5-40 Humidity: 15-85%(No condensation) |
| Labeling accuracy | \pm 1.0mm | Weight | 200Kg |
| Label type | Adhesive sticker, transparent or opaque label | Dimension | 1800(L)*800(W)*1500(H)mm |
| Label roll diameter | Inner diameter: 76mm Outer diameter: 350mm(max) | Remarks | Accept non-standard size customization |