

Vertical Powder Packing Machine HY-90BP

Özellikler :

| | |
|-------------------------|--|
| Fiyat | Contact us |
| Marka Ad? | Hanyi |
| Üretim Yeri | China |
| Minimum Sipari? Miktar? | 1 |
| Ödeme ?artlar? | L/C, T/T, Paypal |
| Tedarik Kapsam? | 1000 |
| Teslimat Detay? | 3days--7days |
| Paketleme Detaylar? | Wooden case or wooden pellets depended on clients' require |

Detayl? Tan?m :

Application

This machine is suitable for fully automatic packaging of powder and other materials.



Main features

The packaging material is controlled by a servo-driven motor, with stable bag length and accurate positioning.

Adopting PID to adjust the temperature controller, the temperature control is more accurate.

PLC is used to control the movement of the whole machine, and the man-machine interface is displayed, which is convenient for operation.

All contact parts are made of SUS304 stainless steel to ensure product hygiene and reliability. Part of the working cylinder adopts original imported parts to ensure accurate and stable work. The additional device of this machine can complete functions such as flat cutting, date printing, and easy tearing.

Technical Parameters

| Model | 420 | 520 | 620 | 720 |
|---------------------------------------|--|--------------------------|--------------------------|--------------------------|
| Sealing form | Back seal. Three-sided seal | | | |
| Measuring range | 20-1000g | 50-1500g | 50-2500g | 100-5000g |
| Bag size | L:50-320mm W:50-200mm | L:50-360mm W:50-250mm | L:50-420mm W:50-300mm | L:50-500mm W:50-350mm |
| Power supply | 380V/50Hz/four-wire/4KW | | | |
| Total Weight | 500KG | 600KG | 700KG | 800KG |
| Machine Overall Dimensions?mm? | 1400*1100*2600 | 1400*1200*2700 | 1400*1300*2800 | 1400*1400*2800 |
| Packaging Material | Made of POPP/PPP, POPP/VMCPP, PPP/PE and other composite materials, such as cellophane, paper, polyester film, aluminum foil, etc. as the base material, coated with composite high-pressure polyethylene. The outer circle is required to be flat, the outer diameter is ?360 mm, the inner diameter of the skeleton = 75 mm, and the film width is ? 420 mm. Operating environment: Temperature -5? ~45?, no freezing. Relative humidity 30-85%, no condensation. | | | |
| Power source | Compressed air (no moisture after filtration) 0.6X105Pa/350L/Min | | | |