

Automatic L-shaped Sealing And Cutting Machine With CE Customized Size Mould

Özellikler:

| Fiyat | Contact Us |
|-------------------------|---|
| Marka Ad? | Hanyi |
| Üretim Yeri | Shanghai, China |
| Minimum Sipari? Miktar? | 1 set |
| Ödeme ?artlar? | T/T |
| Teslimat Detay? | 5 days - 20 days |
| Paketleme Detaylar? | Standard export wooden case or carton box |

Detayl? Tan?m:

Automatic L-shaped sealing and cutting machine



Device description:



- 1. The fully automatic L-shaped sealing and cutting machine is widely used in the production and packaging assembly line, with high work efficiency.
- 2. The cutter adopts Teflon-coated anti-adhesive and high temperature resistant aluminum alloy knife, and the sealing will not split, will not coke, will not smoke, and will cause zero pollution.
- 3. Equipped with imported detection photoelectric and relay. (Using Omron pposite-type Photoelectric).
- 4. Automatic feeding, and the length can be adjusted automatically by a delay switch.
- 5. Equipped with an induction motor to automatically take up waste.
- 6. When the size of the package changes, the adjustment is very simple, and there is no need to change the mold and the bag maker.
- 7. The sealing and cutting knife is equipped with anti-cutting device, so there is no need to worry about the wrong cutting of the package.
- 8. It is suitable for mass shrink packaging in software, photo album, printing, pharmaceutical and other industries.



Packaging machine parameters:

| i dokaging maomilo pa | i dekagnig machine parameters. | | | | |
|-------------------------------------|--------------------------------|-----------------|------------------|--|--|
| Model | L450 | L550 | L650 | | |
| Power supply | 220/50-60HZ | 220/50-60HZ | 220/50-60HZ | | |
| Using electric | 220v | 220v | 220v | | |
| Power | 1.35KW | 1.35KW | 1.7KW | | |
| Packaging speed | 15-30bags/min | 15-30bags/min | 15-30bags/min | | |
| Maximum packaging size H | <150mm | <15mm | <150mm | | |
| Maximum packaging size L+H(H<150mm) | <500mm | <600mm | < 700mm | | |
| Maximum packaging size W+H(H<150mm) | <400mm | <500mm | < 600mm | | |
| Sealing knife size L*W(mm) | 550*450 | 650*550 | 750*650mm | | |
| Machine size (length*width*height) | 1650*800*1450mm | 1750*900*1450mm | 2050*1000*1450mm | | |
| Total Weight | 300kg | 350kg | 400KG | | |
| Trial shrink film | POF/PVC | POF/PVC | POF/PE | | |
| | | | | | |

Shrink furnace



Device Description:

This machine has the functions of automatically wrapping, sealing and cutting, and skin-shrink packaging of single-package products at one time.

The goods packaged by this machine are intuitive, convenient to transport and low in cost. This machine is widely used in the packaging of medicines, food, beverages, stationery, daily necessities, cosmetics, hardware tools, electronic products and other items.

It adopts imported heat-insulating material and imported radiator pipe for heating, and adopts circulating heat dissipation, so that the heating is more even. Power saving and high efficiency (over 15% power saving); the shrinkage temperature and motor transmission speed are stable and adjustable, and the adjustment range is wide; the original air jet device. Therefore, this product has the characteristics of advanced design, extremely stable and reliable performance, good packaging shrinkage effect, novel and beautiful structure, convenient operation and maintenance, etc.



Features:

- A: Protection: It can reduce the possibility of the product being opened and stolen.
- B: Cleanliness: It can avoid contamination with dust, which is especially important for hygiene products and food.
- C: Appearance: It can be packaged with products of different shapes to increase its beauty and sense of value.
- D: Collective: The use of collective packaging has the effect of convenient transportation and purchase of large quantities at a time.
- E: Moisture resistance: It can prevent the relative degree of moisture resistance, especially in cardboard packaging.
- F: Safety and durability: can be in direct contact with food, can protect the original flavor and store for a long time

Shrink furnace parameters:

| Model | BSP4525L | BSP5530L | 6530 Lengthened type | | |
|---|----------------|----------------|----------------------|--|--|
| Power supply | 380v 50-60HZ | 380v 50-60HZ | 380v 50-60HZ | | |
| Power | 10KW | 12KW | 15KW | | |
| Shrink furnace size (length*width*height) | 1500x450x250mm | 1500*550*300mm | 2100*650*300mm | | |
| Product size (width * height) | 400x200mm | 500x250mm | 600*200mm | | |
| Transfer speed | 0-15m/min | 0-15m/min | 0-15m/min | | |



| Conveying material | Mesh belt. Chain roller. Teflon | Mesh belt. Chain roller. Teflon | Mesh belt. Chain roller. Teflon |
|------------------------|---------------------------------|------------------------------------|------------------------------------|
| Conveying load | 25kg max | 25kg max | 25kg max |
| Machine size | 19000x700x1350mm | 1900x800x1500mm | 2500*900*1350mm |
| (length*width*height) | | | |
| Total Weight | 185kg | 260kg | 270kg |
| Applicable shrink film | POF.PVC | POF.PVC | POF.PVC |



Shanghai Hanyi Engineering Equipment Company is one of the most experienced suppliers of filling machines and solutions in China.