

Automatic Batch Number Coding Inkjet Printing Machine For Garment Shops

Özellikler :

Fiyat	Contact Us
Marka Ad?	Hanyi
Üretim Yeri	Shanghai, China
Minimum Sipari? Miktar?	1 set
Ödeme ?artlar?	T/T
Teslimat Detay?	5 days - 20 days
Paketleme Detaylar?	Standard export wooden case or carton box

Detayl? Tan?m :

Description

The first set of high resolution inkjet printer, HP quality, Guaranteed. The ink system and the nozzle are integrally packaged.

No moving parts, no ink leakage, nozzle free maintenance. Except for consumables, there is no other hidden cost.

Supporting PCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DM, QR. Shanghai Hanyi Engineering Equipment Company is one of the most experienced suppliers of inkjet printers in China.



Application Industries: Food, beverage, cosmetics, personal care, medicine and building material market.

Coding Details: Expiration date, MRP, Manufacturing Date, batch number, content, logo, barcode, QR code, two-dimension barcode, data matrix, data base.

Coding Materials: Corrugated paper, coated carton, soft package, hard plastic, envelop, paper carton and liquid container.

Specification

Model	HY-T300 Thermal Inkjet Printer
Display	5-inch color display
Status indication	Ink monitoring, device status, USB application, synchronizer, external photoelectric auto-detection and access
Operating language	Chinese/English (Japanese, French, German, Spanish, Portuguese, Russian, Korean)
Plug and drop card	Adopt HP's latest thermal foam printing technology
Operation interface	Full-color touch screen input, making operation easier
Print content	Date/time, expiry date, counter, box/stack counter, class, barcode, QR code, English, numbers, Chinese, graphics, trademarks, symbols

Support barcode	PCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DM, QR
Printing height	1 to 12.7mm
Data storage capacity	Can store up to 500 data
Print resolution	Standard 300DPI, optional DPI
Input power	AC 90V-240V, 50/60Hz, 12V/3A, 36W (dedicated power adapter)
Best print distance	Freely change the roller according to the needs, less than 6mm
Size (L x W x H)	Controller: 162x92x31mm
	Standard nozzle: 144x95x60 mm
Ink	Volume: 42cc
	Color: Black, red, blue, green, white
	Nature: Water-based, fast-drying, water-based invisible ink, quick-drying invisible ink
USB2.0 interface	Support U disk. Standard
External synchronizer kit	Ensures high print quality when conveyor speed is unstable (Extra charge)
External eye kit	Provide external eye signal (Extra charge)
External three-color warning light	External three-color warning light (Extra charge)
Working conditions	Any normal, non-condensing or harsh environment.
Operating environment	-10-+45°C; 10%-85%RH
Storage environment	-25-+55°C; 10%-90%RH
Warranty	12 months (excluding consumables)